

B-MOUNT 电池



BM-HV300


BM-HV300

容量: 28.8V 10.2Ah 293Wh
 输出: 250W/10A (Max)
 D-TAP*2输出: 16V/4.0A (64W Max), 16V恒压输出
 USB-A输出: 5V/2A
 USB-C输入/输出: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A
 尺寸: 154(L) mm×100(W)mm×87(T)mm
 重量: 1680g




B-mount双路同步充电器-FX-BM2LC

输入: 100~240VAC 47~63Hz
 充电输出: 33.6V/ 3.75A×2
 功率: 280W
 适用于 FXLION B-mount 锂离子电池充电
 尺寸: 230(L)mm×172.92(W)mm×75.5(H)mm
 重量: 1080g



FX-BM24D-V型电池转B-mount输出适配器

输入: 10-29.4V, 可使用14.8V电池和26V电池
 B-Mount输出: 30V/6A (Max), 180W的输出可适配arri super35等摄像机
 2*D-Tap输出: 12V/4A (Max), 12V 恒压输出, 可适配所有的监视器和摄像机外设
 尺寸: 146.5mm×102.5mm×42.8mm
 重量: 380g



BM-HV200


BM-HV200

容量: 28.8V 6.8Ah 196Wh
 D-TAP*2输出: 16V/4.0A (64W Max)
 电池输出: 21.6V~33.6V/250W (Max)
 USB-A输出: 5V/2A
 USB-C输入/输出: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A
 尺寸: 154(L) mm×100(W)mm×68.5(T)mm
 重量: 1150g



B-mount四路同步充电器-FX-BM4LC

输入: 100-240V 47-63Hz
 输出: 33.6V / 3.75A ×4
 功率: 550W
 特点: 四路同步充, 每一路都是4A充电
 尺寸: 245(L) × 154(W) × 170(H)mm
 重量: 3000g



B-mount双路挂板-FX-BM-AR60

ARRI Skypanel S60/S30/S120专用挂板
 输入: 28.8V×2 (电池)
 DC输出: 24.0~33.6V
 尺寸: 319(L)×109(W)×65(H)mm
 重量: 620g

